



Sound Examiner Sound Level Meters SE-401

Knowledge Beyond Measure.



Quest® Sound Examiner dirancang untuk secara akurat mengukur tingkat kebisingan di lingkungan yang sangat bervariasi, termasuk lingkungan yang memerlukan keamanan intrinsik (model -IS). Pengukur ini menghitung tingkat tekanan suara rata-rata (LEQ/LAVG) selama waktu pengoperasian, membantu Anda menilai tingkat kebisingan pekerjaan dan lingkungan dengan lebih akurat. Instrumen SE-401 menampilkan preamp yang dapat dilepas untuk mendukung pemantauan jarak jauh. Model yang aman secara intrinsik memungkinkan pemantauan di lingkungan berbahaya. Semua model siap digunakan tanpa perlu penyetelan.

FITUR

- Mengonfigurasi instrumentasi dan menyimpan penyiapan yang telah dikonfigurasi sebelumnya
- Ambil, unduh, bagikan, dan simpan data instrumen
- Buat bagan, tabel, dan laporan secara intuitif menafsirkan pengukuran Anda
- Ekspor dan bagikan hasil rekaman

REGULASI

Peraturan Menteri Ketenagakerjaan Republik Indonesia
Nomor 5 Tahun 2018
tentang Keselamatan dan Kesehatan Kerja lingkungan kerja

Your Connection for Occupational Health, Safety & Environmental Monitoring



Sound Examiner Sound Level Meters SE-401

SPECIFICATIONS

Measurement

Parameters	SPL, LMax, LMin, LPk (peak), LEQ/LAVG, LE, Elapsed Time
Peak and Frequency weighing	A, C, Z Fast and Slow
Response Time	110 dBA total dynamic measurement range. Overall range 30 – 140 dBA (single range)
Ranges	143 dBA (sampled peak) 3, 4, 5 dBA
Max Peak Level	
Exchange Rates	Run, Stop, Battery Status,
Status Indicators	OL (overload), UR (under-range), Run-Time, Locked Status

Physical

Housing	ABS Polycarbonate IP65. Enclosure rated to IP65. Microphone and external connectors not IP rated.)
Tripod Mount	Standard photographic mount on backside accepts ¼” – 20 screw threads
Drop Protection	Minimum 2 meters onto concrete, 2 times on each face. Acceptable microphone damage.

Power/ Electrical Characteristics

Battery	Lithium Polymer: 2500 mAHr for standard models / 1500 mAHr for IS models, rechargeable Run-Time: 18 hours minimum (excluding the backlight) for standard models / 8 hours for IS Models
Battery life	3 years or 500 cycles (service replaceable)
Batter Charge	USB charger is provided with instrument. Battery charge time: 8 hours (approx.)
Internal memory	2 MB (34 Days at 1 minute logging)
Communications	USB Interface
Standard microphones	Class/ Type 2 General QE 7052
Preamplifier	Preamp directly accepts ½” (132 mm) microphone



Aplikasi dan Market :

- Minyak dan Gas
- Laboratorium Jasa
- Pertambangan
- Perkantoran
- Kontraktor
- Industri Farmasi
- Rumah Sakit

Head Office
 Ruko Mega Cempaka Mas Blok I No. 12
 Jl. Letjend Soepranto, Cempaka Putih
 Jakarta Pusat, Indonesia

Laboratory & Services
 Jl. Cempaka Putih Tengah XVIII No. 12
 Jakarta Pusat, Indonesia

Contact Us
 Marketing : 0821-1183-1227
 Lab Service : 0878-7878-9001
 Hotline : 021-429-0000-7/8
 info@has-environmental.com